

The NeoVolta NV14 is a complete, fully integrated Alternating Current (AC) or Direct Current (DC) Hybrid (120V / 240V) Residential Energy Storage System (ESS). It includes a Lithium Iron Phosphate (LiFePO4) rechargeable battery system for photovoltaic energy conversion and storage, which allows consumers to use their own solar generation after the sun has set. The NV14 also allows consumers to power their homes in grid outages using either their solar or their stored energy in the battery system. The NV14 weighs 560 pounds and has to be ground mounted.

### INVERTER SPECIFICATIONS

BAT Voltage	48 V DC (42 V - 58 V)
BAT Current	175 A DC
AC Voltage	120 V / 240 V AC (Split Phase)
AC Frequency	60 Hz (59.5 Hz - 60.5 Hz)
AC Input/Output Current	32 A AC (grid tie)
AC Input Power	7,680 W

#### Output

Nominal AC Power Output	7,680 W
Max. AC Power Output	8,448 W
Max. Continuous Output Current	32A AC

#### PV Input

Max. AC Power Input Current*	32A AC (7,680 W)
Max. DC PV Power Input (STC)**	8,448 W
MPPTs	2 (2 strings) (5,000 Watts, 500 V & 22 A per MPPT)
MPPT range	Range 125 VDC to 425 VDC
BAT Discharge Power	7,680 W (8,448 W max)

Operating Temperature -25.C to 60.C (>45.C derating)

DC = Direct Current    AC = Alternating Current    W = Watts  
V = Volts                    A = Amps                    Hz = Hertz

\* A higher PV current source may be used up to 40A Continuous (9,600 W).

\*\*A higher PV Power Input may be used up to 10,000 W; the inverter will limit its input to the values stated.

### BATTERY SPECIFICATIONS

#### NOMINAL CHARACTERISTICS

Nominal Voltage	48 V
Typical Capacity	100 Ah (25.C)
Typical Energy	14,400 Wh
Volumetric Density	122.3 Wh/dm
Gravimetric Density	102.1 Wh/Kg

#### ELECTRICAL CHARACTERISTICS

Voltage Window	42.0 V ~ 54.0 V
Max Permanent Discharge Current	120 A
Max Permanent Charge Current	100 A
Energy Charge Efficiency	94% (20.C)


#### OPERATION ENVIRONMENT

Charge Temperature	0.C to 55.C
Discharge Temperature	-20.C to 60.C
Storage Temperature	-20.C to 60.C



QUESTIONS  
**800 364 5464**

[WWW.NEOVOLTA.COM](http://WWW.NEOVOLTA.COM)



The NeoVolta NV24 is an additional 9,600 W battery capacity option that combines with the NV14. Total energy storage capacity is increased from 14.4 kWh to 24.0 kWh of Lithium Iron Phosphate (LiFePO4) rechargeable battery. The NV24 weighs 280 pounds and has to be ground mounted.

### BATTERY SPECIFICATIONS

#### NOMINAL CHARACTERISTICS

Nominal Voltage	48 V
Typical Capacity	100 Ah (25.C)
Typical Energy	9,600 Wh
Volumetric Density	122.3 Wh/dm
Gravimetric Density	102.1 Wh/Kg

#### ELECTRICAL CHARACTERISTICS

Voltage Window	42.0 V ~ 54.0 V
Max Permanent Discharge Current	120 A
Max Permanent Charge Current	100 A
Energy Charge Efficiency	94% (20.C)

#### OPERATION ENVIRONMENT

Charge Temperature	0.C to 55.C
Discharge Temperature	-20.C to 60.C
Storage Temperature	-20.C to 60.C


DC = Direct Current    AC = Alternating Current    W = Watts  
 V = Volts                    A = Amps                    Hz = Hertz



QUESTIONS  
**800 364 5464**

[WWW.NEOVOLTA.COM](http://WWW.NEOVOLTA.COM)

## NV14/24 CYCLE LIFE VS DEPTH OF DISCHARGE (6,000 cycles at 90% DOD)



\*A cycle is considered one full charge and one full discharge.

## NV14/24 ENERGY STORAGE SYSTEM SPECIFICATIONS

- Underwriters Laboratories (UL) 9540, 9540a, 1973, 1741, 1741 SA, 1642, and 1699B Arc Fault Circuit Protection Type 1
- Institute of Electrical and Electronics Engineers (IEEE) 1547 (2003 standard)
- International Electrotechnical Commission (IEC) 62897
- Electrical Codes: National Fire Codes (NEC) 2017
- California Public Utilities Commission (CPUC) Rule 21 Interconnection
- Hawaii Electric Companies Source Requirement Document Version 1.1 (SRD-UL-1741-SA-V1.1)
- CSA Group C22.2 No. 107.1:2001 Ed. 3
- Federal Communications Commission (FCC) 15 Class B
- National Electrical Manufacturers Association (NEMA) Type 3R
- California Energy Commission (CEC): Grid Support Utility, Utility Interactive, Energy Storage System



DISCLAIMER: The information provided herein is correct to the best of NeoVolta's knowledge, is presented in good faith and believed to be correct at the time of printing. No liability for any errors, facts or opinions is accepted. NeoVolta makes no representations or warranties as to the completeness or accuracy of the information. NeoVolta has no liability for any errors or omissions in the materials. NeoVolta, reserve the right to change, delete, or otherwise modify the information which is represented without any prior notice. Persons receiving this information will make their own determination as to its suitability for their own purposes prior to use. In no event will NeoVolta be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this specification sheet or the products to which the information refers. All weights and measures shown are best approximations.



QUESTIONS

**800 364 5464**

[WWW.NEOVOLTA.COM](http://WWW.NEOVOLTA.COM)